

Wet Look Sealer Solvent Based

FILAWET

SEALER
SOLVENT BASED

FILA[®]
surface care solutions

UNPOLISHED NATURAL STONE



PROTECTS SURFACES AGAINST STAINS AND DIRT.

HIGHLY RESISTANT TO UV RAYS AND HEAVY TRAFFIC.



Coverage:

Unpolished natural stone, terracotta

• 215 sq.ft. (20 m²)

Coverage rates are indicative and per coat.



Packaging:

1 QT (946 ml) 5 plastic bottles per box

WHAT IT'S FOR

- Intensifies the color of unpolished natural stone.
- Gives the surface a wet-look, gloss finish.
- Protects the surface from dirt and stains.
- Prevents the penetration of water, grease and oil.
- Ideal for use in kitchens, under barbeques, on driveways and in high traffic areas.

ADVANTAGES

- Does not yellow or flake over time.
- UV resistant.

HOW TO USE IT

Ready to use, no dilution necessary.

Instructions: On a clean, dry surface apply an even coat of FILAWET with a large, flat paintbrush, lambswool applicator or roller. Wait 24 hours and apply a second coat. To achieve a high gloss finish, a third coat may be needed on particularly porous materials.

Maintenance: Dilute FILACLEANER 1:200 (capful per gallon of water). On areas exposed to adverse weather conditions, reapply FILAWET every two years.

Caution: The surface may be walked on 24 hours after the application of the last coat. Do not apply on terracotta floors or polished surfaces. Do not apply the product outdoors if rain is in the forecast. Use FILANOPAINTSTAR to thoroughly clean treated surfaces or if the product has been applied incorrectly.

Fila Chemicals USA, Corp.
Miami, FL 33172
tel +1-305-513-0708
filausa@filasolutions.com

TOLL FREE 1-844-FILA123



Recommended by over
200 INTERNATIONAL TOP BRANDS
manufacturers of materials for floors and wall coverings
usa.filasolutions.com